

## RESIDENTIAL CROSS CONNECTION APPLICATION

LAWN SPRINKLER: New  N       LAWN SPRINKLER: Existing: Y N

SILCOCKS:  Y       NEW SECOND METER: Y N

### HOME OWNER INFORMATION

LOCATION OF METER: \_\_\_\_\_

PROPERTY OWNER: \_\_\_\_\_ TEL NO: \_\_\_\_\_

ADDRESS: \_\_\_\_\_

### PLUMBER/CONTRACTOR INFORMATION

COMPANY NAME: \_\_\_\_\_ TEL NO: \_\_\_\_\_

ADDRESS: \_\_\_\_\_

CONTACT PERSON: \_\_\_\_\_ TEL NO: \_\_\_\_\_

PLUMBER'S EMAIL: \_\_\_\_\_

### BACKFLOW PREVENTION DEVICE INFORMATION

MANUFACTURER: \_\_\_\_\_

TYPE: \_\_\_\_\_ MODEL: \_\_\_\_\_

### CROSS CONNECTION PLAN

*ON REVERSE SIDE OF THIS SHEET, PLEASE PROVIDE A SCHEMATIC, USING ACCEPTED SYMBOLS AND NOMENCLATURE, DETAILING YOUR PROPOSED INSTALLATION. IT IS IMPORTANT THAT THE SCHEMATIC SHOW EITHER: (1) PRESSURE VACUUM BREAKER INSTALLATION -MUST HAVE A MINIMUM OF 12 INCHES ABOVE THE HIGHEST POINT OF WATER IN A SPRINKLER SYSTEM, OR (2) REDUCED PRESSURE ZONE BACKFLOW ASSEMBLY -ASSEMBLY MUST BE INSTALLED A MINIMUM OF 12 INCHES ABOVE GROUND LEVEL.*

SIGNATURE OF APPLICANT: \_\_\_\_\_ DATE: \_\_\_\_\_

### OFFICE USE ONLY

\_\_\_\_\_  
APPROVED BACKFLOW DEVICE  
\_\_\_\_\_  
NOTIFIED PLUMBER/HOMEOWNER  
\_\_\_\_\_  
NOTIFIED PLUMBING INSPECTOR

Date \_\_\_\_\_ Initials \_\_\_\_\_  
Date \_\_\_\_\_ Initials \_\_\_\_\_  
Date \_\_\_\_\_ Initials \_\_\_\_\_